




Rain, Sleet, or Snow, Always on Guard for Your Protection!

JH016 4G Outdoor Security Camera



JH016



Parking Lot



Yard



Street



Wi-Fi + 4G connection

Access live video stream or recorded footage from anywhere at anytime.



Weatherproof

Durable weatherproof casing can withstand the toughest outdoor conditions.



PIR sensor

Trigger auto recording & push notifications when it senses heat



Free Cloud storage

Keep 30 days of motion-triggered recordings for free.



1080P full HD

Crystal clear video quality shows every little detail.



Night vision with IR

Capture detailed black and white infrared video in complete darkness.



Solar powered

Power the camera in sunny day in the event of power outage.

JH016 4G Outdoor Security Camera

Category	Item	Specification
Camera	Image sensor	2 Megapixel CMOS sensor
	Minimum illumination	0.1Lux (IR LED OFF), 0 Lux (IR LED ON)
	Shutter	Environment self-adaptation
	White balance	Automatic
	DNR	3D DNR
	Camera lens	F2.8 aperture; 90° wide angle
	Day & Night switch	ICR
Compress standard	Video compression standard	H.264
	Video compression bitrate	Stream self-adaptation (BR: 0 ---1Mbps)
Image	Image resolution	HD 1080P(1920*1080),864 × 480
	Max framerate	25fps
	Video quality	HD
	Snapshot & record	√
Network	Connection	WiFi (IEEE802.11b/g/n); 4G (FDD-LTE/TDD-LTE); 3G(WCDMA)
	Frequency	4G LTE:B1 B2 B3 B4 B5 B7 B8 B17 B20 B38 B39 B40 B41 GSM:850/900/1800/1900MHZ WCDMA:850/900/1800/1900/2100MHZ
	Protocol	IPV4,UDP,TCP,DHCP,P2P
	Access way	Plug & play (P2P)
	PIR motion sensor	√
	Push notification	√
	Storage APP	Micro SD card (max 64G) and Cloud storage iOS/Android
	OTA	√
	Wireless standards	IEEE802.11b/g/n
	Frequency range	2.4 GHz~2.4835 GHz
Wireless	Channel bandwidth	20/40MHz
	Security	128bit AES
	Transmission rate	11b: 11Mbps; 11g: 54Mbps; 11n: up to 150Mbps
	Transmission distance	30 meters
	CPU	Quad-core 1.3GHz
Others	RAM/ROM	1GB+8GB
	OS	Andriod 4.4
	LED	Three-colour LED
	Working environment	-20℃~50℃, Humidity<95% , No condensation
	Power supply	12V / 2A, Micro USB interface
	Battery (optional)	Built-in 450mAh lithium battery
		External 10Ah lithium battery + Solar panel
	Power consumption	<5W
	IR view distance	10 meters
	PIR	5 -10 meters

Contact

Jimi Electronic Co., Ltd.

Add: 4/F, Building B, Gaoxinqi Industrial Park, Liuxian 1st Road, No.67 Bao'an District, Shenzhen

Tel: +86 755 6664 2520

Web: www.jimilab.com

Email: info@jimilab.com